

# NQR | 17,950 LBS. GVWR CLASS 5

V8 GAS



<b>GVWR/GCWR</b>	17,950/23,950 lbs.
<b>BODY/PAYLOAD ALLOWANCE</b>	11,531 - 12,289 lbs.
<b>GAWR</b>	
Front	6,830 lbs.
Rear	13,660 lbs.
<b>FRONT AXLE CAPACITY</b>	6,830 lbs.
<b>REAR AXLE CAPACITY</b>	14,550 lbs.
Ratio	5.571
<b>SUSPENSION F/R SPRINGS</b>	Tapered/Multi-Leaf
Capacity	8,440/14,550 lbs.
<b>SERVICE BRAKES</b>	Vacuum + Power Assist, Hydraulic
Front/Rear	4-wheel Disk Brakes w/ 4-Channel ABS
<b>FRAME RAIL</b>	
Section Modulus	7.20 in. <sup>3</sup>
Resistance Bending Moment	316,800 lb.-in.
<b>TRANSMISSION</b>	Allison® LCT 1000 6-Speed Automatic
<b>ENGINE</b>	PSI LNJ V8 Gasoline
Displacement	6.0L (365 in. <sup>3</sup> )
Engine Power	311hp @ 4,900 rpm
Engine Torque	353 lb.-ft. @ 4,150 rpm
<b>LIMITED SLIP DIFFERENTIAL</b>	Optional
<b>ALTERNATOR</b>	145-amp
<b>BATTERIES</b>	1 Maintenance-Free Group 31 750-CCA
<b>TIRES LRR</b> (Low Rolling Resistance)	225/70R19.5G (14-pr) Standard
<b>STEERING</b>	Integral Hydraulic Power
<b>STEERING COLUMN</b>	Tilt and Telescopic
<b>FUEL TANK</b>	38.6 gal. in-frame

## 2022 ISUZU N-SERIES

Wheelbase (in.)	Cab to Axle (in.)	Cab to End of Frame (in.)	Back of Cab (in.)	Overall Length (in.)	Body Length (ft.)
<b>STANDARD CAB</b>					
132.5	110	153.1	7.7	224	12-14
150	127.5	170.6	7.7	241.5	14-16
176	153.5	196.6	7.7	267.5	18-20
<b>CREW CAB</b>					
150.0	88.5	131.6	5	241.5	12
176.0	114.5	157.6	5	267.5	16

